

NIGHTOWL Pearl 30W LED Floodlight (IP65)

4000K 2550lm



PRELUX
LED PRODUCTS

Product Code: PXPSP30



IP65




Technical Specifications

Model	Input Voltage	Power	Power Factor	Lumen (±5%)	Beam Angle	CCT	Lifespan	CRI	Dimensions
30W	AC100-240V	30W	≥0.9	2550	110°	4000K	>25000h	70	196.5*215*76mm

Driver Data Sheet

Driver Data	Non-Dimmable
Input Voltage	AC100-240V
Frequency	50-60Hz
Rated Wattage	30W
Electrical Classification	I
Ingress Protection	IP65
Operating Temperature	-20°C~45°C
Operating Humidity	10~75%
Storage Temperature	-30°C~60°C
Cable	40cm



The Prelux Nightowl Pearl 30W LED Floodlight provides up to 70% energy saving compared to traditional non-LED Floods.

The fitting is maintenance free and IP65 rated for all-weather outdoor applications making it ideal for general exterior/ security lighting, garden lighting and commercial/industrial lighting applications. The adjustable bracket enables the beam to be oriented and fixed at the required angle.

- Environment friendly, without Mercury or other hazardous substances
- Up to 70% energy saving compared to traditional floodlights
- Long lifetime of 25,000 hours
- 110° beam angle
- IP65 Protection
- CCT: 4000K



00353 (1) 860 1860 | info@ecilighting.ie | www.ecilighting.ie

