

VERONA 60W Adjustable Downlight

4000K 4080lm



PRELUX LED PRODUCTS

Product Code: PXVER60W4K



Technical Specifications

Model	Voltage	Power	Power Factor	Lumen (±5%)	Beam Angle	CCT	Lifespan	CRI	Dimensions
60W	AC100-240V	60W	≥0.9	4080	60°	4000K	40000h	≥80	L330*W175*H135mm cutout L310*W160mm



Driver Data Sheet

Driver Data	Non-dim
Input Rated Voltage	AC100-240V
Frequency	50/60Hz
Input Voltage	AC85-265V
Efficiency	≥87%
Total Load Wattage	60W±5%
Power Factor	≥0.9
Rated Input Current	≤0.7A
Full Load Output Voltage	DC35-40V
Rated Output Current	1400mA
Output Current Range	1400mA±5%
Power Tolerance	±5%
Current Output Tolerance	±5%
Dimming Range	-
Dimmer	-
Short Circuit Protection	PASS
Over Voltage Protection	PASS
Over Temperature Protection	PASS
Withstand Voltage	AC3750V

Fixture Compatibility

Rated Wattage	60W
Electrical Classification	II
Ingress Protection	IP20
Operating Temperature	-20°C~45°C
Operating Humidity	0~90%
Storage Temperature	-20°C~65°C

Beam Angle



The Verona 60W rectangular LED recessed light is uniquely designed with a COB high power LED chip. A highly efficient reflector with COB LED provides high lumen output and wide beam angle. Adjustable lighting direction offers various lighting orientation.

- Environment friendly, without Mercury or other hazardous substances
- Up to 70% energy saving compared to standard CFL
- Long lifetime of 40,000 hours
- 60° wide beam angle
- L310*W160mm cutout
- CCT: 4000K
- Adjustable and rotary
- No UV/IR light