

Sabre II 51W (5ft) IP65 Datasheet

4000K 5100Lm LED Batten


PXSAB252



Easy Installation




Two Tone Extruded Shell



Double Row LEDs



Stainless Steel Mounting Clips



Input Rated Voltage	AC220-240V
Frequency	50/60Hz
Output Power	51W
LED Type	DOB
Protection Rating	IP65, IK08
Security Class	I
Dimensions	1515*60*52mm
Body Material	Polycarbonate
Diffuser Material	Light Diffusing Polycarbonate
Mounting Material	#301 Stainless Steel
Lamp Weight (Kg)	0.58
Luminous Efficiency	100lm/W
Luminous Flux	5100
Power Factor	>0.96
Beam Angle	120°
CRI	>80
SDCM	≤5
Colour Temperature	4000K
Operating Temperature	-30~+40°C
Certification	CE, CB,
Installation	Suspended/Ceiling
Average Life	50,000h
Power Efficiency	≥85%
Lamp Failure Rate	L70B50 (@25°C)
Warranty	5 Years

Model	L(mm)	W(mm)	H(mm)
51W	1515	60	52

Features & Applications

- IP65 waterproof and IK08 protection grade
- DOB LED with double row arrangement
- Produces a highly efficient 100Lm/W
- High-quality aluminum enhances heat dissipation
- Produces a uniform and soft glow
- SDCM≤5, CRI>80
- Easy Installation - quick connection structure.
- 5 Year Warranty