


## Nico Black 12W Datasheet

4000K 1020Lm LED Track Spotlight


PX12BL4K



Dimensions (mm)	
A	126.5
B	194
C	137.5
D	ø75
E	104



### Beam Angle



Input Rated Voltage	AC100-240V
Frequency	50/60Hz
Input Voltage	AC85-265V
Efficiency	≥83%
Total Load Wattage	12W±1W
Power Factor	≥0.9
Lumen Output ±5%	1020lm
Beam Angle	30°
CCT	4000K
Lifespan	40000h
CRI	≥80
Dimensions	L126.5*W89*H220mm
Rated Input Current	≤0.15A
Full Load Output Voltage	DC30-40V
Rated Output Current	280mA
Output Current Range	280mA±5%
Power Tolerance	±5%
Current Output Tolerance	±5%
Short Circuit Protection	PASS
Over Voltage Protection	PASS
Over Temperature Protection	PASS
Withstand Voltage	AC1500V

### Features & Applications

Prelux Nico track lights adopt COB LEDs with excellent color rendering index to increase the color fidelity of the target illuminated object. It provides excellent heat dissipation and even light output without glare or dark spot. Adjustable lighting orientation with 360 degree in horizontal direction and 180 in vertical direction provided. 1-circuit adapter, 2-circuit adapter, 3-circuit adapter are all available.

- Environment friendly, without Mercury or other hazardous substances
- Up to 70% energy saving compared to standard CFL
- Adjustable 360° degrees horizontally, 180° degrees vertically
- Long lifetime of 40,000 hours
- 30° beam angle
- CCT: 4000K
- No UV/IR light