



## 1500mm Barline 3000K Datasheet

35/40/45/50W 8,000Lm (Max) LED Linear Track Light

PXBAR15003K



<b>Dimensions</b>	1500*28*60mm
<b>Input Voltage</b>	AC220~240V 50/60Hz
<b>Wattage</b>	Power Selectable 35W/40W/45W/50W
<b>Power Factor</b>	≥0.9
<b>Beam Angle</b>	120°
<b>Housing Color</b>	White (RAL 9016)
<b>Luminous Flux</b>	5,600Lm - 8,000Lm
<b>Color Rendering Index</b>	Ra80
<b>Lifetime</b>	50,000Hrs
<b>Fixture Material</b>	Aluminium, PMMA, PC, PVC
<b>Colour Temperature</b>	3000K
<b>Protection Level</b>	IP20
<b>Luminaire Nett Weight</b>	1.15kg
<b>Operating Temperature</b>	-25°C~+40°C
<b>Luminous Efficacy</b>	160Lm/W
<b>Certification</b>	CE, UKCA
<b>Warranty</b>	5 Years

### Features & Applications

With a wide 120° beam angle and contemporary slimline design, the Prelux Barline is ideal for use in retail stores and commercial showrooms.

The Barline range is also exceptionally efficient, producing an impressive 160Lm/W.

It is also compatible with all major 3 circuit track brands including Unipro, Global, Ivela, Eutrac, Stucchi, Powergear and Staff.