




## RGBW 5x4W Floodlight Datasheet

33.6W 1000Lm RGBW 4-in-1 LED

PXLIBFLRGBW20



CE	UK CA	33.6W	IP66	LED	24V
----	----------	-------	------	-----	-----

<b>Dimensions</b>	177x146x505mm
<b>Weight</b>	2.48Kg
<b>Material</b>	Die-cast Aluminium
<b>Colour/Finish</b>	Dark Grey, Powder Coated
<b>IK Rating</b>	IK07
<b>Voltage/Frequency</b>	24V DC
<b>Luminous Flux</b>	1000lm
<b>Luminous Efficacy</b>	29Lm/W
<b>Color Rendering Index</b>	W: >80
<b>CCT Colour Temp</b>	RGB+W: 3000K
<b>SDCM Colour Consistency</b>	W: 6
<b>UGR Unified Glare Rating</b>	-
<b>LEDs</b>	5x4W
<b>Light Control</b>	On/Off
<b>Beam Angle</b>	30°
<b>Adjustable</b>	Yes
<b>Chip</b>	Prolight RGBW 4-in-1
<b>Maintained Luminous Flux</b>	L80 (B10) 30,000h
<b>Warranty</b>	3 Years

### Features & Applications

- RGBW 4-in-1 Colour Temperature
- 24V DC
- Power Cable 2m H05RN-F 5 x 0.5mm
- Dimensions 177x146x505mm

Options Available	
DMX Controls	Available on Request