



Lineout 38W Standard Datasheet

4ft Colour Temperature Selectable 5130lm LED Batten



PXLINE438CCT



Push fit terminal block for fast installation.



Gear tray retaining strap for easy maintenance.



Dimensions	1171*63*72mm (4ft)
Weight (Kg)	1.4kg
Material	Steel Body, PC Diffuser
Colour/Finish	White
IK Rating	08
Voltage/Frequency	220-240V 50HZ
Luminous Flux	5130lm
Luminous Efficacy	135lm/W
Color Rendering Index	80
CCT Colour Temp	3000K/4000K/6000K
SDCM Colour Consistency	<4
UGR Unified Glare Rating	<22
LEDs	Everlight
Light Control	On/Off
Beam Angle	120°
Adjustable	Fixed
Chip	Epistar
Maintained Luminous Flux	L80 (B10) 50,000h
Warranty	5 years

Features & Applications

The Prelux Lineout CCT is a highly efficient LED batten which produces an impressive 125lm/W and provides instant full light.

The Lineout comes with a push fit terminal block for fast and hassle free installation as well as a gear tray retaining strap to allow for easy maintenance.

The luminous efficacy and 5 year warranty of the Lineout makes it an ideal fitting for public buildings such as libraries, schools and hospitals as well as private commercial offices and retail stores.