



Lineout 60W Standard Datasheet

6ft Colour Temperature Selectable 8100lm LED Batten



PXLINE660CCT



Push fit terminal block for fast installation.



Gear tray retaining strap for easy maintenance.



Dimensions	1732x62x74mm
Weight (Kg)	1.9kg
Material	Steel Body, PC Diffuser
Colour/Finish	White
IK Rating	IK08
Voltage/Frequency	220-240V 50HZ
Luminous Flux	8,100lm
Luminous Efficacy	135lm/W
Color Rendering Index	>80
CCT Colour Temp	3000K/4000K/6000K
SDCM Colour Consistency	<4
UGR Unified Glare Rating	<22
LEDs	Everlight
Light Control	On/Off
Beam Angle	120°
Adjustable	Fixed
Chip	Epistar
Maintained Luminous Flux	L80 (B10) 50,000h
Warranty	5 years

Features & Applications

The Prelux Lineout CCT is a highly efficient LED batten which produces an impressive 135lm/W and provides instant full light.

The Lineout comes with a push fit terminal block for fast and hassle free installation as well as a gear tray retaining strap to allow for easy maintenance.

The luminous efficacy and 5 year warranty of the Lineout makes it an ideal fitting for public buildings such as libraries, schools and hospitals as well as private commercial offices and retail stores.